

PRO-009

# CERAMIC PAINT

## PRODUCT DATA SHEET

PRO-009 Ceramic Paint is a high-quality internal paint formulated with ceramic components and high-quality polymer resin to provide a durable, smooth and attractive decorative finish.

Once dry, it forms a hard, dense coating with excellent scratch resistance, strong colour durability and high resistance to washing, scrubbing and non-aggressive detergents. The low-VOC, hypoallergenic formulation also has a pleasant fragrance, making it well-suited to interior spaces that require both durability and a high-quality finish.

### Intended Uses

PRO-009 Ceramic Paint is intended for internal use on walls and ceilings where a durable, washable decorative coating is required. It is especially suitable for heavily used interior spaces such as staircases, bathrooms, kitchens and public-use environments including nurseries, offices, hospitals and similar buildings. The paint is suitable for use on correctly prepared cement-lime plasters, gypsum plasters, plasterboard, concrete, reinforced concrete, finishing coats and suitably prepared existing paint coatings.



### Technical Specification

#### Composition

Ceramic components, additives, titanium white, pigments and polymer dispersion.

#### Quantity per Unit

2.5 L

#### Consumption

Approx. 0.1 l/m<sup>2</sup>

#### Gloss Level

Matt

#### Density

Approx. 1.35 g/cm<sup>3</sup>

#### Application Temperature

+5°C to +30°C

#### Drying Time

Approx. 2 hours (6 hours before next coat)

#### Water Vapour Diffusion

Category V2 (EN 1062-1), sd value 0.25m

#### Wet Scrub Resistance

Class 1 (EN 13300)

Please note: These figures may vary based on the substrate and application method.

Please see the reverse of this page for directions for use.

# Directions for use

## Substrate Preparation

Substrates must be dry, sound, clean and free from dust, grease, release agents, paint residues, mould, algae, moss, saline efflorescence and other contaminants that may affect adhesion. Any symptoms of biological growth should be removed before painting. Surface irregularities, cracks and cavities should be repaired using materials suitable for the substrate, and repair areas must be fully dry and properly set before decoration. Surfaces not intended for painting should be protected prior to application. As a guide, cement-lime plasters should be painted after a minimum of 28 days, gypsum plasters after 14 days, gypsum smoothing coats after 3 days and polymer smoothing coats after 2 days of drying.

## Product Preparation

PRO-009 Ceramic Paint is supplied ready to use. Do not dilute with water or mix with other materials. Stir thoroughly before use and check that the selected colour matches requirements before application begins.

## Application

Apply the paint evenly by roller, brush or suitable spray equipment. Paint continuously across each full surface to avoid visible lap marks and do not allow individual sections to dry out part-way through application. Use paint from the same production batch on one continuous surface wherever possible. Where additional coats are required, allow the previous coat to dry for a minimum of 6 hours before applying the next.

## Application Conditions

Apply when air, substrate and product temperatures are between +5°C and +30°C. Rooms should be ventilated during application and drying, but strong draughts that could cause excessive drying should be avoided. High humidity and lower temperatures may significantly extend drying times.

## Clean-up

Tools and equipment should be cleaned with clean water immediately after use.

## Packaging & Storage

PRO-009 Ceramic Paint is supplied in 2.5 litre units. Store in original, sealed packaging in dry conditions at temperatures between +5°C and +25°C. When stored correctly, shelf life is up to 24 months from the date of manufacture.

## Compliance with Standards

The declared water vapour diffusion performance is Category V2 in accordance with EN 1062-1, with an sd value of 0.25 m. Wet scrub resistance is classified as Class 1 in accordance with EN 13300.

## Safety Measures

Avoid contact with skin and eyes during use. In the event of eye contact, rinse immediately with plenty of clean water and seek medical advice. Suitable gloves, safety goggles and protective clothing are recommended during application.

## General Information

This data sheet replaces all previous editions. The information provided is based on current knowledge and practical experience, and while it has been compiled with care, it is not guaranteed to be accurate, complete or suitable for all applications. It is the responsibility of the user to verify the product's suitability for their specific use case. No legal obligations are established by this document.

Data Sheet Revision Date: 24/03/2026



### Address:

Unit 1-2 King George's Trading Estate,  
Davis Road,  
Chessington,  
England,  
KT9 1TT

### Email:

info@ewipro.com

### Phone:

0800 133 7072



EWIPRO



www.ewipro.com